

ADA Series

Ionising Radiation Detector

ADA-I ADA-2

Comply with ANSI™ 42.33/1, 42.32 ve IEC 62401.



4 Years Warranty

Color TFT Display

English and Turkish Menu

Long Battery Life

User Friendly Menu

Shock Proof Silicone Case

Dose Rate and Cumulative Dose in Single Screen

Adjustable Sv/h, Gy/h, R/h, rad/h, rem/h, CPM, CPS units

Audible and Vibrant, Dose Rate and Cumulative Dose Alarm



DISPLAY: Color TFT Display
BATTERY: 2x1.5V AA
WEIGHT: 220 gr (with protective case)
DIMENSIONS: 84 x 154 x 30 mm
TUBE: Geiger Muller (GM)
BUZZER: 85 dB @ 1m

	ADA-1	ADA-2
RADIATION TYPE:	Gamma, X-Ray	Gamma, X-Ray, Beta, Alpha
DOSE RATE RANGE:	0-20 mSv/h	0-2 mSv/h
CUM. DOSE RANGE:	0-99 Sv	0-99 Sv
ENERGY SENSITIVITY:	beta 150 keV, >%25 gamma/X-ray min. 40keV -	beta 150 keV, >%75 gamma/X-ray min. 40keV alpha 3.6 MeV
ACCURACY:	% \pm 15	% \pm 10
SENSITIVITY:	32 CPM/ $\mu\text{Sv/h}$	108 CPM/ $\mu\text{Sv/h}$

MANUFACTURER
ALARA Radiaton Safety Consulting Ltd.
Bagdat Cad. Trion Plaza 505/10
Maltepe/Istanbul
Phone: (0216) 482 00 36 Fax: (0216) 482 87 38
www.alarargd.com